




AKAI


MODEL VX90


SCHEMATIC DIAGRAM AND PC BOARDS












TABLE OF CONTENTS

1. CONTROL BLOCK DIAGRAM.....	2
2. VOICE & CHORUS BLOCK DIAGRAM.....	3
3. CONNECTION DIAGRAM.....	4
4. AMP PCB, CONTRAST PCB, DIN JACK PCB, JACK PCB, OPERATION PCB, POWER SW PCB, POWER SUPPLY PCB, PROTECT SW PCB, TUNE & OUTPUT PCB, VALUE VR PCB	5
5. CPU SCHEMATIC DIAGRAM	6
6. CPU PCB.....	7
7. VOICE SCHEMATIC DIAGRAM	8
8. VOICE PCB	9
9. CHORUS SCHEMATIC DIAGRAM.....	10
10. CHORUS PCB	11
11. ICs	12












B = PNP TRANSISTOR
 B = NPN TRANSISTOR

WARNING: Δ INDICATES SAFETY CRITICAL COMPONENTS FOR CONTINUED SAFETY.
 REPLACE SAFETY CRITICAL COMPONENTS ONLY WITH MANUFACTURER'S
 RECOMMENDED PARTS.
 AVERTISSEMENT: Δ IL INDIQUE LES COMPOSANTS CRITIQUES DE SÉCURITÉ.
 POUR MAINTENIR LE DEGRÉ DE SÉCURITÉ DE L'APPAREIL.
 NE REMPLACER QUE DES PIÈCES RECOMMANDÉES PAR LE FABRICANT



VX90 CPU
SCHEMATIC DIAGRAM
No.4-2 860739B



LOCATION OF COMPONENTS

IC1 --- A1 IC12 --- A2
IC2 --- A1 IC13 --- B1
IC3 --- B1 IC14 --- D1
IC5 --- B1 IC15 --- C2
IC6 --- C1 IC16 --- C1
IC7 --- C1 IC17 --- C2
IC8 --- D1 IC18 --- A2
IC9 --- D1 IC19 --- B2
IC10 --- D2 IC20 --- C1
IC11 --- D2 IC21 --- C2

PHI --- B2


TR1 --- A2

TR2 --- A2

TR4 --- C2

TR1,2 --- 2SC3383

TR4 --- 2SC3330



2SC3383




2SC3330

CPU PCB LI013A5010

8
[Symbol] = NPN TRANSISTOR

WARNING: INDICATES SAFETY CRITICAL COMPONENTS FOR CONTINUED SAFETY. REPLACE SAFETY CRITICAL COMPONENTS ONLY WITH MANUFACTURER'S RECOMMENDED PARTS.
AVERTISSEMENT: INDIQUE LES COMPOSANTS CRITIQUES DE SÉCURITÉ. POUR MAINTENIR LE DEGRÉ DE SÉCURITÉ DE L'APPAREIL, NE REMPLACER QUE DES PIÈCES RECOMMANDÉES PAR LE FABRICANT.



VOICE PCB LI013A5040

TO CHORUS PCB ③

IC1 : G-1	IC11 : F-2	IC21 : E-1	IC31 : A-2	IC41 : D-4	TR1 : G-2	2SC3400.....TR1,2,3
IC2 : G-2	IC12 : F-3	IC22 : A-1	IC32 : B-2	IC42 : C-4	TR2 : G-2	2SC3330.....TR4
IC3 : G-3	IC13 : F-3	IC23 : B-1	IC33 : C-2	IC43 : B-4	TR3 : G-3	2SC3383.....TR5,TR14,TR15
IC4 : G-4	IC14 : F-3	IC24 : C-1	IC34 : D-2	IC44 : B-4	TR4 : F-1	
IC5 : F-1	IC15 : F-3	IC25 : D-1	IC35 : D-2	IC45 : A-4	TR5 : E-1	
IC6 : F-1	IC16 : F-3	IC26 : E-1	IC36 : E-2		TR14 : D-4	
IC7 : F-1	IC17 : F-3	IC27 : E-1	IC37 : A-3		TR15 : E-4	
IC8 : F-2	IC18 : F-4	IC28 : A-1	IC38 : C-3			
IC9 : F-2	IC19 : F-4	IC29 : C-1	IC39 : E-3			
IC10 : F-2	IC20 : E-4	IC30 : E-1	IC40 : E-4			




2SC3400
2SC3330





2SC3383

VX90



VX90 CHORUS
SCHEMATIC DIAGRAM
NO.4-4 860741C (A2)

B
 = PNP TRANSISTOR
 B
 = NPN TRANSISTOR

ECB



 2SC3330
 2SA1317
 2SC3401


SGD

 2SK381


LOCATION OF COMPONENTS

IC's	TR's	
IC1	A1	TR3
IC2	A1	TR4
IC4	B3	TR5
IC5	B3	TR8
IC6	A3	TR10
IC7	A4	TR11
IC8	A3	TR12
IC9	A3	TR13
IC11	B1	TR14
IC12	B2	TR15
IC13	B2	TR16
		TR17
		TR18







74LS04P (Hex INVETOR)




74LS38P (QUAD 2 INPUT OC NAND BUFFER)




M5218L




74LS14P (Hex SCHMIT TRIGGER INVETOR)



74LS32P (QUAD 2 INPUT OR GATE)




74LS42P (BCD TO DECIMAL DECODER)



FUNCTION TABLE

NO.	INPUTS				OUTPUTS									
	D	C	B	A	0	1	2	3	4	5	6	7	8	9
0	L	L	L	L	L	H	H	H	H	H	H	H	H	H
1	L	L	L	H	L	H	H	H	H	H	H	H	H	H
2	L	L	H	L	L	H	H	H	H	H	H	H	H	H
3	L	L	H	H	L	H	H	H	H	H	H	H	H	H
4	L	H	L	L	L	H	H	H	L	H	H	H	H	H
5	L	H	L	H	L	H	H	H	L	H	H	H	H	H
6	L	H	H	L	L	H	H	H	L	H	H	H	H	H
7	L	H	H	H	L	H	H	H	L	H	H	H	H	H
8	H	L	L	L	L	H	H	H	H	L	H	H	L	L
9	H	L	L	H	L	H	H	H	H	L	H	L	L	L
INVALID	H	L	H	L	L	H	H	H	H	H	H	H	H	H
	H	L	H	H	L	H	H	H	H	H	H	H	H	H
	H	H	L	L	L	H	H	H	H	H	H	H	H	H
	H	H	L	H	L	H	H	H	H	H	H	H	H	H
	H	H	H	L	L	H	H	H	H	H	H	H	H	H
	H	H	H	H	L	H	H	H	H	H	H	H	H	H


74LS139 (DUAL 2 TO 4 DEMULTIPLEXER)




FUNCTION TABLE

INPUTS		OUTPUTS			
ENABLE	SELECT	Y0	Y1	Y2	Y3
H	X	X	X	X	X
L	L	L	L	L	L
L	L	L	L	L	L
L	L	L	L	L	L
L	L	L	L	L	L
L	L	L	L	L	L


74LS373 (OCTAL 3 STATE D-LATCH)



TC4051BP/CD4051BE



TC4066BP



FUNCTION TABLE

C IN	IMPEDANCE BETWEEN IN/OUT - OUT/IN
H	0.5 to 5 x 10 ² OHMS
L	MORE THAN 10 ⁹ OHMS